



JMU 137 QW

Universal magnetic core drill up to 1-3/8 in [35 mm]

Small, long-stroke, single-speed universal magnetic core drill with forward / reverse rotation and maximum functionality for flexible work on the construction site.

Product number: 7 270 54 61 12 0

Details

- > Extremely wear-resistant tool concept with swivel-mounted motor cable protection hose for tough conditions in industry and skilled trades.
- > Perfect power-to-weight ratio, thanks to compact, weight-optimized design and FEIN 1 100 W high-performance motor with tacho electronics for high speed stability for reliable and efficient operation.
- > Right/left rotation, electronic speed adjustment and 10-1/4 [260] in[mm] stroke range enable universal work applications such as core drilling, spiral drilling, tapping as well as countersinking and reaming.
- > Small and lightweight.
- > Simple and error-proof control concept in the operator's field of view.
- > Easy to read convenient magnetic holding force display.
- > High magnetic holding force.
- > Motion sensor.
- > Additional magnet switch in the drill stand.
- > Integrated coolant tank.
- > Hand feed wheel can be mounted on either side.
- > "Memory function" speed storage.

Price includes

- ✓ 1 coolant tank
- ✓ 1 chip hook
- ✓ 1 chip guard
- ✓ 1 safety strap
- ✓ 1 pilot pin
- ✓ 1 case

Product feature

- ✓ Magnet holding force display
- ✓ Electronic speed setting
- ✓ Speed-controlled tacho electronics
- ✓ Forward/reverse operation
- ✓ Memory function
- ✓ Tilt sensor

Application



Mag base drilling metal up to 1-3/8 in dia.



Twist drills with drill chuck



Tapping



Countersinking



Reaming



Performing overhead work



Installation work



Workshop jobs



★ suitable
★★ well suitable

Technical data

TECHNICAL DATA

Power consumption	1,100 W
Power output	550 W
Full load speed	130 - 520 rpm
Carbide cutter max. dia.	1-3/8 [35] in[mm]
HSS cutter max. dia.	1-3/8 [35] in[mm]
Cutter max. drilling depth	2 [50] in[mm]
Twist drill max. dia.	5/8 [16] in[mm]
Tapping	M 14
Max. countersinking dia.	1-1/4 [31] in[mm]

VIBRATION AND SOUND EMISSION VALUES

Sound pressure level LpA Measurement uncertainty of the measured value KpA	82,3 dB 5 dB
Sound power level LWA Measurement uncertainty of the measured value KWA	93,3 dB 5 dB
Peak sound value LpCpeak Measurement uncertainty of the measured value KpCpeak	95,9 dB 5 dB
Vibration value 1 α_{hv} 3-way Measurement uncertainty of the measured value K α	$\alpha_{h,D} < 2,5 \text{ m/s}^2$ 1,5 m/s ²

Reaming max. dia.	5/8 [16] in[mm]
Cutter holder	3/4" Weldon
Cutter change	tool-free
Stroke	5-5/16 [135] in[mm]
Total stroke range	10-1/4 [260] in[mm]
Magnetic holding force	2248 [10,000] lbs[N]
Magnetic holding force	10,000 N
Magnetic base dimensions	6-7/8 [175] x 3-1/8 [80] in[mm]
Magnetic base dimensions	175 x 80 mm
Cable with plug	13.1 [4] ft[m]
Weight	23.59 [10.70] lbs[kg]
Weight	23.59 lbs

Application examples

